


TUBI SALDATI TONDI

da nastro laminato a caldo

UNI 7811

| ØD \ S | 1,5 | 2 | 2,5 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
|--------|------|------|-------|-------|-------|-------|-------|-------|-------|--------|--------|
| 12 | 0,39 | | | | | | | | | | |
| 14 | 0,46 | | | | | | | | | | |
| 16 | 0,54 | 0,69 | | | | | | | | | |
| 18 | 0,61 | 0,79 | | | | | | | | | |
| 19 | 0,65 | 0,84 | | | | | | | | | |
| 20 | 0,68 | 0,89 | | | | | | | | | |
| 22 | 0,76 | 0,99 | | | | | | | | | |
| 25 | 0,87 | 1,13 | 1,39 | 1,63 | | | | | | | |
| 28 | 0,98 | 1,28 | 1,57 | 1,85 | | | | | | | |
| 30 | 1,05 | 1,38 | 1,70 | 2,00 | | | | | | | |
| 32 | 1,13 | 1,48 | 1,82 | 2,15 | | | | | | | |
| 35 | 1,24 | 1,63 | 2,00 | 2,37 | | | | | | | |
| 38 | 1,35 | 1,78 | 2,19 | 2,59 | 3,35 | | | | | | |
| 40 | 1,42 | 1,87 | 2,31 | 2,74 | 3,55 | | | | | | |
| 42 | 1,49 | 1,97 | 2,43 | 2,88 | 3,75 | | | | | | |
| 45 | 1,61 | 2,12 | 2,62 | 3,11 | 4,04 | | | | | | |
| 48 | 1,72 | 2,27 | 2,80 | 3,33 | 4,34 | 5,34 | | | | | |
| 50 | 1,79 | 2,37 | 2,93 | 3,48 | 4,54 | | | | | | |
| 52 | 1,87 | 2,47 | 3,05 | 3,63 | 4,74 | | | | | | |
| 55 | 1,98 | 2,61 | 3,24 | 3,85 | 5,03 | | | | | | |
| 57 | 2,05 | 2,71 | 3,36 | 4,00 | 5,23 | | | | | | |
| 60 | 2,16 | 2,86 | 3,56 | 4,21 | 5,52 | 6,78 | | | | | |
| 62 | 2,24 | 2,96 | 3,67 | 4,37 | 5,72 | 7,03 | | | | | |
| 63 | 2,27 | 3,01 | 3,73 | 4,44 | 5,82 | 7,17 | | | | | |
| 65 | 2,35 | 3,11 | 3,85 | 4,59 | 6,02 | 7,40 | | | | | |
| 70 | 2,53 | 3,35 | 4,16 | 4,96 | 6,51 | 8,01 | | | | | |
| 76 | 2,76 | 3,65 | 4,54 | 5,41 | 7,11 | 8,77 | 10,37 | | | | |
| 80 | 2,90 | 3,85 | 4,78 | 5,70 | 7,50 | 9,25 | 10,95 | | | | |
| 83 | 3,01 | 4,00 | 4,96 | 5,92 | 7,80 | 9,62 | 11,40 | | | | |
| 89 | 3,23 | 4,29 | 5,33 | 6,36 | 8,38 | 10,35 | 12,27 | 14,14 | 15,96 | | |
| 96 | | 4,64 | 5,76 | 6,88 | 9,08 | 11,22 | 13,32 | 15,36 | | | |
| 102 | | 4,93 | 6,13 | 7,32 | 9,67 | 11,96 | 14,21 | 16,40 | 18,47 | | |
| 108 | | 5,23 | 6,50 | 7,77 | 10,26 | 12,70 | 15,09 | 17,44 | | | |
| 114 | | 5,52 | 6,87 | 8,21 | 10,90 | 13,44 | 15,99 | 18,48 | 20,97 | 23,37 | 25,72 |
| 121 | | 5,87 | 7,31 | 8,73 | 11,45 | 14,31 | 17,02 | 19,69 | | | |
| 127 | | 6,17 | 7,68 | 9,17 | 12,13 | 15,04 | 17,90 | 20,72 | 23,48 | 26,19 | 28,85 |
| 133 | | | 8,05 | 9,62 | 12,73 | 15,78 | 18,83 | 21,76 | | | |
| 139 | | | 8,42 | 10,06 | 13,32 | 16,53 | 19,69 | 22,80 | 25,98 | 29,01 | 31,99 |
| 152 | | | 9,22 | 11,05 | 14,64 | 18,18 | 21,66 | 25,10 | 28,49 | 31,83 | 35,12 |
| 159 | | | | 11,54 | 15,69 | 18,99 | 22,64 | 26,24 | 29,79 | 33,29 | 36,75 |
| 168,3 | | | 10,23 | 12,23 | 16,21 | 20,14 | 24,02 | 27,85 | 31,63 | 35,36 | 39,04 |
| 177,8 | | | | 12,93 | 17,14 | 21,31 | 25,42 | 29,49 | 35,50 | 37,47 | 41,38 |
| 193,7 | | | | 14,11 | 18,71 | 23,27 | 27,77 | 32,23 | 36,64 | 40,99 | 45,30 |
| 219,1 | | | | 15,99 | 21,22 | 26,40 | 31,53 | 36,61 | 41,65 | 46,63 | 51,57 |
| 244,5 | | | | | 23,72 | 29,53 | 35,29 | 41,00 | 46,66 | 52,27 | 57,83 |
| 273,0 | | | | | 26,54 | 33,05 | 39,51 | 45,92 | 52,28 | 58,60 | 64,86 |
| 323,9 | | | | | 31,56 | 39,32 | 47,04 | 54,71 | 62,32 | 69,89 | 77,41 |
| 339,7 | | | | | | 41,27 | 49,38 | 57,43 | 65,44 | 73,40 | 81,31 |
| 355,6 | | | | | | 43,23 | 51,73 | 60,18 | 68,58 | 76,93 | 85,23 |
| 406,4 | | | | | | 49,50 | 59,25 | 68,95 | 78,60 | 88,20 | 97,76 |
| 457,2 | | | | | | | 66,76 | 77,72 | 88,62 | 99,48 | 110,29 |
| 508,0 | | | | | | | 74,28 | 86,49 | 98,65 | 110,75 | 122,81 |



TUBI SALDATI TONDI

da nastro laminato a caldo

UNI 7811

| 2 | $\varnothing D$ | S* | Kg/m |
|-------|-----------------|------|-------|
| 3/8" | 16,75 | 1,8 | 0,66 |
| 1/2" | 21,25 | 2,2 | 1,03 |
| 3/4" | 26,75 | 2,5 | 1,50 |
| 1" | 33,5 | 2,65 | 2,02 |
| 1 ¼ " | 42,4 | 3 | 2,91 |
| 1 ½ " | 48,3 | 3 | 3,35 |
| 2" | 60,3 | 3 | 4,24 |
| 2 ½ " | 76,1 | 3 | 5,41 |
| 3" | 88,9 | 3 | 6,36 |
| 3 ½ " | 101,6 | 3 | 7,29 |
| 4" | 114,3 | 3 | 8,23 |
| 4 ½ " | 127 | 3,7 | 11,26 |
| 5" | 139,7 | 3,7 | 12,41 |
| 5 ½ " | 152 | 4 | 14,61 |
| 6" | 168 | 4 | 16,18 |
| 7 ½ " | 193,7 | 4 | 18,65 |
| 8" | 219 | 5 | 26,40 |

* Spessore per impieghi più correnti.
I tubi possono tuttavia essere forniti anche con spessore diverso.